



Wall Chargers
for charging and operating your meter

Order Number:
[CHG1,4, or U]

We have a charger to meet your operational need. Summit Technology's PowerSight meters operate on internal rechargeable batteries. To supply the needs for various PowerSight models and the different power standards of the world, there are several models to choose from. The table below guides you in your choice of wall power supplies.

Charger Model	PowerSight Compatibility	Power Standard	Description
CHG1	All meters except PS3000 (HW < 6.1)	European 220V/50Hz	A barrel plug output charger to supply 12VDC @ 500mA. [order CHG1]
CHG4	All meters except PS3000 (HW < 6.1)	N. America 120V/60Hz	A barrel plug output charger to supply 12VDC @ 500mA. [order CHG4]
CHGU	All meters except PS3000 (HW < 6.1)	Universal 100V-240V	A charger with interchangeable adapters to supply 12VDC @ 500mA [order CHGU]

Please note: Other charger styles are available upon request.

CHG4



CHGU



Please note: For operating and charging your meter off of the power that is being monitored, see our line-to-DC converters, LDC2, LDC3, and LDC4.

Availability

Chargers are available for immediate purchase from Summit Technology Inc. To order, specify the charger model.

For more information on our products contact:

Summit Technology Inc.
 2246 Monument Blvd.
 Pleasant Hill, CA 94523-3453

Voice: 1-925-944-1212
 Email: sales@powersight.com

PowerSight® is a trademark of Summit Technology. Prices and specifications are subject to change without notice.